



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISION		DESCRIPTION	DATE	CHANGED BY	APPROVED
ZONE	REV	A	INITIAL RELEASE	03/06/2023	HBAKKE PHOSODAR





D

D



C

C



RECOMMENDED
PANEL CUTOUT

NOTES:

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY.
2. DUST CAPS NOT SHOWN.
3. RECOMMENDED PANEL THICKNESS: .05-.07" [1.2-1.7mm]
4. STANDARDS: IEC 61754-20, TIA/EIA 604-10A-2002, TELCORDIA GR-326-CORE
5. INSERTION LOSS: <0.2dB
6. OPERATING/STORAGE TEMPERATURE: -40 TO +85°C
7. COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

REGULATORY COMPLIANCE:

EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]

OVERALL CABLE LENGTH TOLERANCE:
 ≤ 12 [305] = +1 [25] / -0
 > 12 [305] ≤ 60 [1524] = +2 [51] / -0
 > 60 [1524] ≤ 120 [3048] = +4 [102] / -0
 > 120 [3048] ≤ 300 [7620] = +6 [152] / -0
 > 300 [7620] = +5% / -0

ALL OTHER DIMENSIONAL TOLERANCES:

$.X = \pm .2$ [5] FRACTIONS
 $.XX = \pm .02$ [5] $\pm 1/32$
 $.XXX = \pm .005$ [13] ANGLES $\pm 1^\circ$



APPROVALS

DRAWN BY
HBAKKE

03/06/2023

CHECKED BY
DMAY

03/06/2023

APPROVED BY
REVANGELIS

03/06/2023

DATE

03/06/2023

03/06/2023

03/06/2023



50 High Street, West Mill,
North Andover, MA 01845 USA.
Phone: 1.800.341.5266
1.978.682.6936

CATEGORY

FIBER OPTICS

CONFIGURATION DETAILS OF
UNDIMENSIONED FEATURES
MAY VARY

ANGLES $\pm 1^\circ$

FRACTIONS
 $\pm 1/32$



PRODUCT DESCRIPTION

Fiber Coupler, LC/LC SlimLine Quad, Translucent Internal Shutter,
Side Spring, High Density Reduced Height, No Flange, Black

SIZE

A

CAGE CODE

43321

ITEM NO.

FOA-834-BLK

REV.

A

SCALE: NONE

CAD FILE: FOA-834-BLK.SLDDRW

SHEET 1 OF 1