

Lead Free LSZH Bend Relief 3-Slot TRB Plug to Plug  
for 78 Ohm TWCH-78-2-LC, 48" Cable



## LC3MSA00580-48

### Configuration

- Connector 1: TRB 3-Slot Plug
- Connector 2: TRB 3-Slot Plug
- Cable Type: TWCH-78-2-LC

### Features

- MIL-STD-1553
- -30°C to +80°C
- 78 ohms
- ROHS Low Smoke Zero Halogen
- Non-Toxic

### Applications

- Military Contractors
- MIL-STD-1553
- Data
- Safer Environments
- Ventilation critical areas
- Hospitals

### Description

L-com's LC3MSA00580-48 is a lead free LSZH bend relief 3-Slot TRB plug to plug for 78 Ohm TWCH-78-2-LC, 48" cable and ships same-day. These flexible RF cable assemblies are ideal for applications where flexure is required. Our L-com TRB 3-Slot to TRB 3-Slot cable assembly has a plug to plug gender configuration with 78 Ohm flexible TWCH-78-2-LC series coax and operates to 500 MHz.

Custom versions of this TRB 3-Slot plug to TRB 3-Slot plug cable, along with the rest of L-com's other RF assemblies, can also be built and shipped same day. Other available RF cable assembly value added services from L-com include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly. Contact a sales representative for testing or custom RF cable quotes. Part number LC3MSA00580-48 L-com Lead Free LSZH Bend Relief 3-Slot TRB Plug to Plug for 78 Ohm TWCH-78-2-LC, 48" Cable data sheet PDF includes details of the RF product specifications, CAD drawing(s) and dimensions below.

### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		500	MHz
Capacitance		21.2 [69.55]		pF/ft [pF/m]
Operating Voltage (AC)			1,000	Vrms

### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	10	50	100	200	500	MHz
Insertion Loss (Typ.)	0.29	0.41	0.5	0.62	0.84	dB

#### Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

Lead Free LSZH Bend Relief 3-Slot TRB Plug to Plug  
for 78 Ohm TWCH-78-2-LC, 48" Cable



## LC3MSA00580-48

### Mechanical Specifications

#### Cable Assembly

Length*	48 in [121.92 cm]
Weight	0.256 lbs [116.12 g]

#### Cable

Cable Type	TWCH-78-2-LC
Impedance	78 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper, Silver
Dielectric Type	PE
Shield Layer 1	Silver Plated Copper
Jacket Material	HF POF, Blue
One Time Minimum Bend Radius	1.25 in [31.75 mm]

### Connectors

Description	Connector 1	Connector 2
Type	TRB 3-Slot Plug	TRB 3-Slot Plug
Impedance	78 Ohms	78 Ohms
Contact Material and Plating	Bronze, Gold 30 micro inches	Bronze, Gold 30 micro inches
Contact Plating Specification	ASTM-B-488	ASTM-B-488
Dielectric Type	Teflon	Teflon
Outer Conductor Material and Plating	Phosphor Bronze, Gold	Phosphor Bronze, Gold
Outer Conductor Plating Specification	30 micro inches	30 micro inches
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	ASTM-B-733	ASTM-B-733

### Environmental Specifications

#### Temperature

Operating Range -30 to +80 deg C

### Compliance Certifications

(see [product page](#) for current document)

### Plotted and Other Data

Notes:


Lead Free LSZH Bend Relief 3-Slot TRB Plug to Plug  
for 78 Ohm TWCH-78-2-LC, 48" Cable



## LC3MSA00580-48

### How to Order

Part Number Configuration:



Example: LC3MSA00580-12 = 12 inches long cable  
LC3MSA00580-100cm = 100 cm long cable

Lead Free LSZH Bend Relief 3-Slot TRB Plug to Plug for 78 Ohm TWCH-78-2-LC, 48" Cable from L-com has same day shipment for domestic and International orders. L-com is a leading manufacturer of wired and wireless connectivity products and committed to in-stock availability and same day shipping. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

Lead Free LSZH Bend Relief 3-Slot TRB Plug to Plug for 78 Ohm TWCH-78-2-LC, 48" Cable

L-com CAD Drawing


# LEAD FREE SOLDER

The diagram illustrates a cable assembly. At the bottom, a **2X TRB 3-SLOT PLUG** is shown. Above it, a **2X BEND RELIEF** section is depicted as a coiled spring. The main cable body is labeled **LENGTH** and features a **LABEL SEE NOTE 1** section containing the text **WWW.L-COM.COM** and **LXXXXX**. The top of the cable is a **78 OHM TWINAX CABLE** jacket, with the model number **TWCH-78-2** and other specifications: **JACKET: FR HALOGEN, BLUE** and **NOM. DIA.: 242" [6.15]**.

## NOTES.

1. CABLE ASSEMBLY LENGTH LABEL PLACEMENT: 36 INCHES OR LESS, ONE LABEL APPROXIMATELY CENTERED. LONGER THAN 36 INCHES, TWO LABELS APPROXIMATELY 6 INCHES FROM EACH CONNECTOR.
2. CABLE ASSEMBLIES SHALL BE TESTED FOR CONTINUITY.
3. CABLE ASSEMBLY LENGTH DETERMINED BY PN AS ILLUSTRATED  
IC3MSA00580-XX (XXX = OAL IN INCHES)

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED.

 		<p>INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5</p> <p>SCALE      SHEET</p> <p>NONE      1 OF 1</p>	
<p>UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE IN THOUSANDS OF INCHES. MILLIMETER DIMENSIONS IN ALL MILLIMETERS.</p> <p><math>X = \pm 0.2 [5]</math>      FRACTIONS  <math>XX = \pm 0.02 [0.5]</math>      <math>\pm 1/32</math>  <math>XXX = \pm 0.005 [0.13]</math>      ANGLES <math>\pm 1^\circ</math></p> <p>TOLERANCES:</p> <p>CABLE LENGTH TOLERANCES:</p> <p><math>\pm 12 [305] = +1 [25] / -0</math>  <math>\pm 15 [381] = +2 [38] / -0</math>  <math>\pm 20 [508] = +4 [102] / -0</math>  <math>\pm 30 [762] = +6 [152] / -0</math>  <math>\pm 50 [1270] = +10 [254] / -0</math>  <math>\pm 80 [1981] = +16 [381] / -0</math>  <math>\pm 120 [2954] = +24 [508] / -0</math>  <math>\pm 180 [4064] = +36 [762] / -0</math>  <math>\pm 250 [5890] = +50 [1270] / -0</math>  <math>\pm 350 [8380] = +70 [1981] / -0</math>  <math>\pm 500 [11930] = +100 [2954] / -0</math>  <math>\pm 700 [16010] = +140 [4064] / -0</math>  <math>\pm 1000 [21910] = +200 [5890] / -0</math></p> <p>DESCRIPTION</p> <p>LEAD FREE LSZH BEND RELIEF 3-SLOT TRB PLUG TO PLUG FOR 78 OHM TWICH-78-2 CABLE</p>			
<p>ITEM NO.</p> <p>LC3MSA00580</p>	<p>REV</p> <p>A</p>		

LC3MSA00580-48 REV 1.0 | © 2020 Infinite Electronics, Inc. L-com is a registered trademark of Infinite Electronics, Inc.