

HyperLink Wireless Brand 5.8 GHz 27dBi High Performance Die Cast Aluminum Reflector Grid Antenna - Model: HG5827EG

Features

- Superior Performance
- UV Stable Light Gray Powder Coat Finish
- All Weather Operation
- Light weight cast aluminum construction
- Two piece design

Applications

- 5.8 GHz 802.11a/n Wireless LAN Systems
- 5.8 GHz UNII and ISM Applications
- Long-Range Directional Applications
- Point to Point, Point to Multi-point Systems
- Wireless Bridges and Backhaul Applications



Description

Superior Performance

The HyperLink HG5827EG High-Performance Reflector Grid WiFi Antenna is ideal for long-range highly directional 5.8 GHz 802.11a/n applications. These antennas are ideal for point to point systems, point to multi-point and wireless bridges. Its compact design makes it nearly invisible in most installations, and it can be installed for either vertical or horizontal polarization.

Rugged and Weatherproof

The antennas' construction features a die cast aluminum reflector grid for superior strength and lightweight. The 2-piece reflector grid is simple to assemble and significantly reduces shipping costs. The grid surface is UV powder coated for durability and aesthetics. The open-frame grid design minimizes wind loading.



This antenna is supplied with a tilt and swivel mast mount kit. This allows installation at various degrees of incline for easy alignment. They can be adjusted up or down from 0° to 60°.

Specifications

Mechanical Specifications

Connector	N Female
Weight	3.35 lbs (1.52kg)
Grid Dimensions	15.75" x 23.62" (400mm x 600mm)
Mounting Mast Diameter	1.58" x 1.97" (40-50MM)

Electrical Specifications

Frequency	5725-5850 MHz
Gain	27dBi
Horizontal Beamwidth	6°
Vertical Beamwidth	9°
Polarization	Vertical or Horizontal
Impedance	50 Ohm
F/B Ratio	25dB
Max. Input Power	100 Watts
VSWR	< 1.5
Lightning Protection	DC Short

Wind Loading Data

Wind Speed (MPH)	Loading
100	20.0 lb.
120	31.0 lb.

RF Antenna Patterns

