

902 to 928 MHz RFID Flat Panel Antenna, RHCP,
9 dBi, White ABS, N Female, IP54



LCANFP1033

Features

- High Performance Multi-tag read/write Capabilities
- Concealable Design
- Right Hand Circular Polarized
- 902 to 928 MHz Frequency Range
- Type N Female Connector
- IP54 Rated

Applications

- Radio Frequency Identification
- Inventory Management
- Access Control
- Data Collection
- Asset Tracking
- Livestock Management

Description

L-Com's LCANFP1033 is a RHCP RFID flat panel antenna. The LCANFP1033 with a 9 dBi gain nominal is a Directional antenna. Our 902 to 928 MHz antenna has N Female connector and is IP54 Rated.

With an impedance of 50 Ohms and max input power of 50 Watts, the LCANFP1033 flat panel RHCP antenna is well suited for Radio Frequency Identification tag reading applications. This 902-928 MHz 9 dBi gain RFID antenna is highly directional providing the reader radio the capabilities of simultaneously reading a multitude of RFID tags with a high degree of accuracy.

L-Com's RFID LCANFP1033 has a radome made of ABS in White color. This N Female connectized Antenna has an overall length of 10 in, width of 10 in, and weighs 1.05 lbs. Use our on-line ordering system to purchase your LCANFP1033 RFID Directional RHCP antenna 24 hours a day with same-day shipping and no MOQs (minimum order quantities).

Configuration

Design	Flat Panel
Application Band	RFID
Band Type	Single
Radiation Pattern	Directional
Polarization	RHCP
Connector Type	N Female
Lightning Protection	Direct Ground

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	902		928	MHz
Input VSWR			1.3:1	
Impedance		50		Ohms
Gain		9		dBi
Horizontal (Azimuth) HPBW		65		Degrees
Vertical (Elevation) HPBW		65		Degrees
Input Power			50	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[902 to 928 MHz RFID Flat Panel Antenna, RHCP, 9 dBi, White ABS, N Female, IP54 LCANFP1033](#)

902 to 928 MHz RFID Flat Panel Antenna, RHCP,
9 dBi, White ABS, N Female, IP54



LCANFP1033

Axial Ratio	2	dB
-------------	---	----

Mechanical Specifications

Radome Material	ABS
Size	
Length	10 in [254 mm]
Width	10 in [254 mm]
Height	1.3 in [33.02 mm]
Weight	1.87 lbs [848.22 g]

Environmental Specifications

Temperature	
Operating Range	-40 to +55 deg C
Ingress Protection	IP54

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

902 to 928 MHz RFID Flat Panel Antenna, RHCP, 9 dBi, White ABS, N Female, IP54 from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

