

806 - 960 MHz / 1710 - 2700 MHz, 9 / 10 dBi, Log Periodic Antenna, Low PIM, V-pol, Type N Female connector



LCANLP1016

Features

- Frequency coverage for 806 MHz to 2700 MHz
- Very High Gain 10 dBi Low PIM Directional Antenna
- Each connector covers wide band of frequencies
- Easy Install universal mounting bracket provided
- Weatherproof ABS – UV Resistance PVC radome
- Pigtail - 8 inches
- N-Type Female connector

Applications

- Point-to-point, LPWAN, LoRA, LTE-M, NB-IoT, IoT, M2M applications
- 5G / 4G LTE B1 to B10, B12 to B20, B23, B24, B25, B28 / 3G / GSM / AWS / WLAN operation supported
- 5G Bands supported
- DAS (Distributed Antenna Systems)
- IEEE 802.11a / b / g / n / ac / ad / ah / ax Wi-Fi applications
- Public safety, utilities, CCTV and local radio coverage
- Smart cities expansion for coverage and IOT / IIOT

Description

The L-com LCANLP1016 is a high performance, wideband log periodic antenna designed to operate from 806 to 2700 MHz for point to point communications. The LCANLP1016 from L-com has 10 dBi of gain and can be used for long distance directional communication over a wide range of frequencies. The LCANLP1016 is ideal for boosting 5G, LTE, CMDA, LoRA, IoT, WIFI.

The log periodic LCANLP1016 has 65 vertical beamwidth and 80 horizontal beamwidth. This antenna has Vertical polarization and the included mounting brackets allow for either vertical or horizontal mounting configurations. Log periodic antennas function as boosters where the existing cellular signal is weak and needs to reach further distances. The L-com directional antenna has a 8 inches long pigtail terminated with 1 Type N Female connector.

L-com's 806 to 2700 MHz log periodic LCANLP1016 antenna with 10 dBi max gain for 5G DAS networks operates in bands n1, n2, n3, n5, n7, n8, n18, n20, n25, n26, n30, n34, n38, n39, n40, n41, n53, n65, n66, n67, n70, n80, n81, n82, n84, n86, n89, n90, n91, n92, n93, n94, n95, n97, n98. This 5G directional log periodic antenna with N Female Type connector is in stock and ready to ship the same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on antennas or other L-com products.

Configuration

Design	Log Periodic
Band Type	Multi
Radiation Pattern	Directional
Polarization	Vertical
Cable Type	RG58U
Cable Length	7.87 in [199.9 mm]
Connector Type	N Female
Number of Ports	1

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	806		2,700	MHz
Input VSWR		1.7:1	2:1	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [806 - 960 MHz / 1710 - 2700 MHz, 9 / 10 dBi, Log Periodic Antenna, Low PIM, V-pol, Type N Female connector LCANLP1016](#)

806 - 960 MHz / 1710 - 2700 MHz, 9 / 10 dBi, Log Periodic Antenna, Low PIM, V-pol, Type N Female connector



LCANLP1016

Impedance		50	Ohms
Gain	9	10	dBi
Horizontal Beamwidth	60	80	Degrees
Vertical Beamwidth	50	65	Degrees
Input Power		100	Watts

Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.806 to 0.96	1.71 to 2.7				GHz
Gain	9	10				dBi
Horizontal HPBW	80	60				Degrees
Vertical HPBW	65	50				Degrees
VSWR Max	2:1	1.7:1				
Maximum Input Power	100	100				Watts

Mechanical Specifications

Radome Material	ABS
Width	8.27 in [210.06 mm]
Height	11.61 in [294.89 mm]
Weight	1.54 lbs [698.53 g]

Environmental Specifications

Temperature	
Operating Range	-40 to +60 deg C
Wind Survivability	150 MPH [241.4 KPH]
Wind Loading	23.5 lbs at 100 MPH 36.2 lbs at 125 MPH

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

806 - 960 MHz / 1710 - 2700 MHz, 9 / 10 dBi, Log Periodic Antenna, Low PIM, V-pol, Type N Female connector from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers,

806 - 960 MHz / 1710 - 2700 MHz, 9 / 10 dBi, Log Periodic
Antenna, Low PIM, V-pol, Type N Female connector

LCANLP1016



passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

REVISIONS		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	03/31/2022
		APPROVED K.HIETPAS

N FEMALE CONNECTOR

7.9 [200] COAX PIGTAIL

2.0 [50] MAX POLE

15.2 [387]

11.6 [295]

LABEL ILS-100-03 (SEE NOTE 1)

2.5 [64]

2.4 [60]

2.5 [64]

8.3 [210]

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE IN INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ±.2 [5.08] FRACTIONS ± 1/32

.XX = ±.02 [.51] ANGLES ± 1°

.XXX = ±.005 [.13] CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] < L ≤ 60 [1524] = ±1 [25] / -0

60 [1524] < L ≤ 120 [3048] = ±4 [102] / -0

120 [3048] < L ≤ 300 [7620] = ±6 [152] / -0

300 [7620] < L = +5% / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

THIRD-ANGLE PROJECTION

THE INFORMATION AND DIMENSIONS SHOWN ON THIS DRAWING IS THE PROPERTY OF L-COM GLOBAL CONNECTIVITY. ALL RIGHTS RESERVED.

SHEET 1 OF 1

SCALE N/A

ITEM NO. L-CANLP1016

REV A

DRAWN BY K.GLEBOVA

CAGE CODE A 43321

E-mail: CustomerService@l-com.com

Website: www.l-com.com

Fax: 1.978.682.6936

Phone: 1.800.341.5266 | 1.978.682.6936

North Andover, MA 01845 USA.

an INFINITE brand

50 High Street, West Mill, 3rd Floor, Suite #30

L-com™

NOTES:
1. LABEL PER ILS-100-03 (FOR INTERNAL REFERENCE ONLY)
LABEL LOCATION FOR REFERENCE ONLY.