

2.4 GHz to 2.5 GHz Stubby Antenna, Monopole, 90-degree angle, RPSMA Male Connector, 2 dBi Gain

LCANRBD1045



Features

- · 2400-2500 MHz, 2 dBi Gain
- 90-degree RP-SMA male connector
- · Plug and play

Applications

- · 2.4 GHz Wi-Fi and ISM applications
- WLAN applications
- · IOT, Wireless audio/video systems
- · Home automation
- · Telemetry, remote monitoring

- VSWR < 2:1
- · Linear polarization
- Monopole antenna
- · Wireless data acquisition
- 802.11 b/g/n, wireless hotspots
- · PtP and PtMP applications
- 5G Band: n53

Description

The L-com LCANRBD1045 is an omni antenna operating from 2.4 GHz to 2.5 GHz with 2 dBi gain. The RP-SMA male connector on the communication antenna enables it to be used vertically, at a right angle, or at any angle in between. Our rubber duck antenna is 0.37 inches wide, 2.01 inches long, and 0.37 inches tall. Our stubby omni antenna is specifically stocked to be available for same business day shipment.

This monopole omnidirectional antenna has a linear polarization, an RP-SMA male connector and an ABS radome material. Our 2 dBi gain LCANRBD1045 antenna transmits high power signals, increasing the signal strength, thus providing improved coverage, better broadcast control, and faster speed. L-com single-band antenna has a gain of 2 dBi antenna for the 2.4 GHz to 2.5 GHz frequency range. Our black omnidirectional antenna functions between -40 to 65 degrees C and has 50 Ohm impedance.

L-com WiFi antenna is ideal for 2.4 GHz Wi-Fi and ISM applications, WLAN, Bluetooth, IOT, wireless audio systems, home automation, telemetry, remote monitoring, wireless data acquisition, 802.11 a/b/g/n/ax, wireless hotspots. These 2 dBi antennas have a waterproof design, a high power handling capacity, and IP65 ingress protection rating. Our high-quality LCANRBD1045 omnidirectional antenna has a maximum input VSWR of 2:1, which results in the best power transfer and reduced losses.

The 2 dBi gain omni directional antenna is just one of many fiber optic products that are available from L-com for international and domestic orders. We are a global leader in wired and wireless connectivity products, offering a wide range of solutions across many key industries, including electronics, medical, industrial automation, military, and telecommunication. L-com also stocks a wide selection of 2.4 GHz to 2.5 GHz antennas that ship same-day from our warehouse.

Configuration

Design Band Type Radiation Pattern Polarization Connector Type Rubber Duck Single Omni Directional Linear SMA Male Reverse Polarity

Electrical Specifications

Description Minimum Typical Maximum Units

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4 GHz to 2.5 GHz Stubby Antenna, Monopole, 90-degree angle, RPSMA Male Connector, 2 dBi Gain LCANRBD1045



2.4 GHz to 2.5 GHz Stubby Antenna, Monopole, 90-degree angle, RPSMA Male Connector, 2 dBi Gain

LCANRBD1045

Frequency Range	2,400		2,500	MHz
Frequency Range Input VSWR Impedance			2:1	
Impedance		50		Ohms
Gain		2		dBi
Input Power			10	Watts

Mechanical Specifications

Radome Material ABS

Size

 Length
 2.01 in [51.05 mm]

 Width
 0.37 in [9.4 mm]

 Height
 0.37 in [9.4 mm]

 Weight
 0.0154 lbs [6.99 g]

Environmental Specifications

Temperature

Operating Range -40 to +65 deg C Storage Range -40 to +80 deg C

Environment Waterproof Ingress Protection IP65

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

2.4 GHz to 2.5 GHz Stubby Antenna, Monopole, 90-degree angle, RPSMA Male Connector, 2 dBi Gain from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

L-com CAD Drawing

