



an INFINIT® brand



2W/5dB RF Fixed Attenuator, SMA Male to SMA Female Passivated Stainless Steel Body Up to 6 GHz

RF Fixed Attenuators Technical Data Sheet

LCAT1000-05

Features

- SMA connector interface
- DC to 6 GHz Frequency Range
- Attenuation 5±0.5 dB
- Max Power 2 Watt (CW)
- VSWR < 1.2:1

Applications

- Instrumentation
- RF test systems
- Prototyping and characterization
- Production systems
- Precision measurements

Description

L-com carries a wide range of fixed attenuators with a broad selection of attenuation levels and frequency ranges. RF fixed attenuators lower the amplitude of a signal (attenuate) by specific amount and can be used in a wide variety of applications. These attenuators are used when signal levels need to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to optimal power range.

Few RF components are as commonly used as fixed coaxial attenuators, and L-com carries one of the largest in-stock varieties and ships them same day. The 5 dB Fixed Attenuator LCAT1000-05 is rated to 2 Watts and operates from DC to 6 GHz. The versatile coaxial package uses SMA male to SMA female connectors and is also RoHS compliant.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|---|---------|---------|---------|-------|
| Frequency Range | DC | | 6 | GHz |
| Impedance | | 50 | | Ohms |
| Nominal Attenuation | | 5 | | dB |
| Attenuation Accuracy | | 0.5 | | dB |
| VSWR | | | 1.2:1 | |
| Input Power, Peak 5µs pulse @ 0.01% duty cycle | | | 200 | Watts |
| Input Power, CW 10% @ 125°C FROM 25°C | | | 2 | Watts |

Mechanical Specifications

Size

| | |
|---------------------------|----------------------------|
| Length | 0.86 in [21.84 mm] |
| Width/Diameter | 0.312 in [7.92 mm] |
| Weight | 0.01027 lbs [4.66 g] |
| Body Material and Plating | Passivated Stainless Steel |

Configuration

| | |
|--------|-------|
| Design | Fixed |
|--------|-------|



an INFINIT® brand



2W/5dB RF Fixed Attenuator, SMA Male to SMA Female Passivated Stainless Steel Body Up to 6 GHz

RF Fixed Attenuators Technical Data Sheet

LCAT1000-05

Connectors

| Description | Connector 1 | Connector 2 |
|--------------------------------------|----------------------------|----------------------------|
| Type | SMA Male | SMA Female |
| Contact Material and Plating | Beryllium Copper, Gold | Beryllium Copper, Gold |
| Outer Conductor Material and Plating | | Passivated Stainless Steel |
| Coupling Nut Material and Plating | Passivated Stainless Steel | |
| Hex Size | 5/16 inch | |
| Body Material and Plating | Passivated Stainless Steel | Passivated Stainless Steel |

Environmental Specifications

Temperature

Operating Range

-65 to +125 deg C

Compliance Certifications

Plotted and Other Data


Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume any liability arising out of the use of any part or documentation.

LCAT1000-05 CAD Drawing

2W/5dB RF Fixed Attenuator, SMA Male to SMA Female Passivated Stainless Steel Body Up to 6 GHz

| REVISIONS | | |
|-----------|-----------------|-----------------------|
| REV. | DESCRIPTION | DATE |
| A | INITIAL RELEASE | 05/23/2019 |
| | | APPROVED BPUCHASKI |



| | | | | |
|--|-------------|---|-------------|---|
| UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS | |  an INFINITO brand 50 High Street, West Mill, 3rd Floor, Suite #30 North Andover, MA 01845 USA Phone: 1.800.341.5266 1.978.682.6836 Fax: 1.978.689.9484 www.L-com.com e-mail: CustomerService@L-com.com | | THE INFORMATION AND DESIGN HEREON IS THE PROPERTY OF L-COM GLOBAL CONNECTIVITY. ALL RIGHTS RESERVED. SHEET 1 OF 1 SCALE N/A |
| TOLERANCES: | FRACTIONS | DRAWN BY | PART NUMBER | |
| X== 2 [5.08] | ± 1/32 | BPUCHASKI | LCAT1000-05 | |
| .XX== .01 [.25] | ± 1/64 | | | |
| .XXX== .005 [.13] | ANGLES ± 1° | | | |
| ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. | | SIZE | REV | |
| THIRD ANGLE PROJECTION | | A | A | |

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

T-Rev.B