

Compact Infrared Temperature Sensor, range 600°C, 4-20mA



SRTH600-405-2807 Compact Infrared Temperature Sensor

Features

- · Simple installation
- · Optimized lens
- · 304 Stainless steel housing
- · 32-bit CPU

Applications

- · Power equipment
- Metallurgy
- · Construction industry
- · Chemical production

- · Fast response
- High accuracy
- · Long-term stability
- Automation systems
- · Petrochemical industry
- · Textile industry
- · Food processing

Description

1

The SRTH600-405 series of infrared temperature sensors feature a compact design allowing for fast, continuous temperature measurement in space constrained areas. The aluminum housing, high sensitivity and fast response time of these rugged sensors make them well suited for use in automation and other industrial applications where contactless temperature sensing is needed. The L-com SRTH600-405 series is part of the IoT portfolio of products available from L-com, in-stock and ready to ship. Contact our knowledgeable technical support and sales staff for more information on this, and other IoT products from L-com.

General Specifications


Application: Infrared Temperature Sensing

Mounting: Bracket, fastened by M18 locking nuts

Electric Connector: flying leads
Sensing Element: Infrared
Emissivity: 0.95
Optical Distance Ratio 20

Output Signal: 4-20mA
Cable Length: 3 m
Humidity: 10-90%

Repeatability: ±1% or ±1°C whichever is greater



Description	Minimum	Typical	Maximum	Unit	
Accuracy (Temperature)		±2		%	
Temperature Range	0		600	deg C	
Spectral Range	8		14	um	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Compact Infrared Temperature Sensor, range 600°C, 4-20mA SRTH600-405-2807



Compact Infrared Temperature Sensor, range 600°C, 4-20mA



SRTH600-405-2807 Compact Infrared Temperature Sensor

Electrical Specifications

Description	Minimum	Typical	Maximum	Unit	
Power Supply Voltage	12	24	30	VDC	
Response			300	msec	

Material Specifications

Description	Material	
Casing	Aluminum alloy	
Cable Material	PVC	

Environmental Specifications

Temperature (Operating) 0deg C to 60deg C
Temperature (Storage) -20deg C to 80deg C

Ingress Protection IP65

Certifications

ROHS Compliant

CE Compliant

The Infinite Electronics portfolio includes coaxial cable assemblies, connectors, adapters and custom products, as well as our wireless product line which includes antennas, RF amplifiers, lightning and surge protectors, and NEMA rated enclosures.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume any liability arising out of the use of any part or documentation.

