

SMA Male Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable



#### TC-240-SM-SS-X-LC



# Times Microwave Systems Connector Specification

## Configuration

- SMA Male Connector
- MIL-STD-348
- 50 Ohms
- · Straight Body Geometry

- LMR-240, LMR-240-DB, LMR-240-FR, 240-Series Interface Type
- Crimp/Solder Attachment

#### **Features**

- · Designed to industry standard interface dimensions
- · Quality body materials and plating

· Crimp/Solder attachment

## **Applications**

- · RF Boxes and components
- · RF Test systems

- General Purpose RF Interconnect
- · Laboratory applications

## Description

L-com's SMA Male connector for LMR-240, LMR-240-DB, LMR-240-FR and 240-Series coax uses a Crimp/Solder attachment method. This SMA connector is one of the many RF coaxial connectors in L-com's product line up and like all our products, they will ship the same day. Our SMA Male connector operates in the frequency range supported by LMR-240 coax.

The specifications and a basic dimensional drawing for TC-240-SM-SS-X-LC Male SMA connector can be found in this datasheet PDF. L-com's portfolio of RF and microwave connectors allows users to choose from a large number of options when building assemblies to fit their RF interconnect needs. RF cables can be created to fulfill many interconnect applications ranging from In the Box hookup, test equipment connectivity or as part of a system installation. In addition to an offering of RF connectors and coaxial cable L-com offers both standard and custom cable assemblies to fit a customer's specific needs.

## **Mechanical Specifications**

#### Size

Length	1.17in	[29.72mm]
Width/Dia.	0.312in	[7.92mm]
Weight	0.021lbs	[9.53g]

#### **Material Specifications**

Description	Material	Plating	
Contact	Beryllium Copper	Gold	
		ASTM B488	
Insulation	Teflon		
Body	Passivated Stainless Steel		
		SAE-AMS-2700	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable TC-240-SM-SS-X-LC



SMA Male Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable



#### TC-240-SM-SS-X-LC



Coupling Nut

Passivated Stainless Steel

SAE-AMS-2700

## **Environmental Specifications**

Compliance Certifications (see product page for current document)

## **Plotted and Other Data**

SMA Male Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components. Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable TC-240-SM-SS-X-LC

URL: https://www.l-com.com/sma-male-connector-crimp-solder-attachment-lmr-240-lmr-240-db-lmr-240-series-cable-tc-240-sm-ss-x-lc-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.ontained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

## **L-com CAD Drawing**

