

## TNC Male Right Angle Connector for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable



### TC-240-TM-RA-D-LC

#### Times Microwave Systems Connector Specification

##### Configuration

- TNC Male Connector
- 50 Ohms
- Right Angle Body Geometry
- Connector Interface Types: LMR-240, LMR-240-DB, LMR-240-FR, 240-Series

##### Features

- Designed to industry standard interface dimensions
- Quality body materials and plating
- Crimp/Solder attachment
- Operates to 6 GHz

##### Applications

- RF Boxes and components
- RF Test systems
- General Purpose RF Interconnect
- Laboratory applications

##### Description

L-com's TNC Male connector for LMR-240, LMR-240-DB, LMR-240-FR and 240-Series coax uses a Crimp/Solder attachment method. This TNC connector is one of the many RF coaxial connectors in L-com's product line up and like all our products, they will ship the same day. Our TNC Male connector operates up to a maximum frequency of 6 GHz.

The specifications and a basic dimensional drawing for TC-240-TM-RA-D-LC Male TNC connector can be found in this datasheet PDF. L-com's portfolio of RF and microwave connectors allows users to choose from a large number of options when building assemblies to fit their RF interconnect needs. RF cables can be created to fulfill many interconnect applications ranging from In the Box hookup, test equipment connectivity or as part of a system installation. In addition to an offering of RF connectors and coaxial cable L-com offers both standard and custom cable assemblies to fit a customer's specific needs.

#### Electrical Specifications

| Description            | Minimum | Typical | Maximum | Units |
|------------------------|---------|---------|---------|-------|
| Frequency Range        | DC      |         | 6       | GHz   |
| VSWR                   |         |         | 1.35:1  |       |
| Insertion Loss         |         |         | 0.15    | dB    |
| Operating Voltage (AC) |         |         | 500     | Vrms  |
| Impedance              |         | 50      |         | Ohms  |

#### Mechanical Specifications

##### Size

|        |                     |
|--------|---------------------|
| Length | 1.21 in [30.73 mm]  |
| Width  | 0.57 in [14.48 mm]  |
| Height | 1.16 in [29.46 mm]  |
| Weight | 0.066 lbs [29.94 g] |

## TNC Male Right Angle Connector for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable



### TC-240-TM-RA-D-LC

#### Material Specifications

| Description  | Material | Plating |
|--------------|----------|---------|
| Contact      | Brass    | Gold    |
| Insulation   | Teflon   |         |
| Body         | Brass    | Nickel  |
| Coupling Nut | Brass    | Nickel  |

#### Environmental Specifications

##### Temperature

**Compliance Certifications** (see [product page](#) for current document)

#### Plotted and Other Data

Notes:


TNC Male Right Angle Connector for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable from L-com has same day shipment for domestic and International orders. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

URL: <https://www.l-com.com/tnc-male-right-angle-connector-lmr-240-lmr-240-db-lmr-240-fr-240-series-cable-tc-240-tm-ra-d-lc-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

# TC-240-TM-RA-D-LC CAD Drawing

TNC Male Right Angle Connector for LMR-240, LMR-240-DB, LMR-240-FR, and 240-Series Cable



T-Rev D