

Lead Free 1553 TRB 2-Slot Plug to Blunt Cut Genderless Cable Assembly using M17/176-00002 Coax, 5 FT with Bend Relief

LC3MSA00465-60



Configuration

- Connector 1: TRB 2-Slot Plug
- Connector 2: Blunt Cut Genderless
- Cable Type: M17/176-00002

Features

- MIL-STD-1553
- -55°C to +200°C
- 78 ohms

Applications

- Vehicle High Temperature
- Data
- MIL-STD-1553

Description

L-com's LC3MSA00465-60 is a lead free 1553 TRB 2-Slot plug to blunt cut genderless cable assembly using M17/176-00002 coax, 5 FT with bend relief and ships same-day. These flexible RF cable assemblies are ideal for applications where flexure is required. Our L-com TRB 2-Slot to Blunt Cut cable assembly has a plug to genderless gender configuration with 78 Ohm flexible M17/176-00002 series coax and operates to 10 MHz.

Custom versions of this TRB 2-Slot plug to TRB 2-Slot genderless cable, along with the rest of L-com's other RF assemblies, can also be built and shipped same day. Other available RF cable assembly value added services from L-com include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly. Contact a sales representative for testing or custom RF cable quotes. Part number LC3MSA00465-60 L-com Lead Free 1553 TRB 2-Slot Plug to Blunt Cut Genderless Cable Assembly using M17/176-00002 Coax, 5 FT with Bend Relief data sheet PDF includes details of the RF product specifications, CAD drawing(s) and dimensions below.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		10	MHz
Capacitance		24 [78.74]		pF/ft [pF/m]
Operating Voltage (AC)			750,000	Vrms

Insertion Loss (Typ.)
Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

Mechanical Specifications

Cable Assembly

Length*	60 in [152.4 cm]
Weight	0.11 lbs [49.9 g]

Cable

Cable Type	M17/176-00002
Impedance	78 Ohms

Lead Free 1553 TRB 2-Slot Plug to Blunt Cut Genderless Cable Assembly using M17/176-00002 Coax, 5 FT with Bend Relief

LC3MSA00465-60



Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper, Silver
Dielectric Type	PTFE
Shield Layer 1	Silver Plated Copper
Jacket Material	PFA, Blue
One Time Minimum Bend Radius	1.5 in [38.1 mm]

Connectors

Description	Connector 1	Connector 2
Type	TRB 2-Slot Plug	Blunt Cut Genderless
Impedance	78 Ohms	
Contact Material and Plating	Bronze, Gold 30 micro inches	
Contact Plating Specification	ASTM-B-488	
Dielectric Type	Teflon	
Outer Conductor Material and Plating	Phosphor Bronze, Gold	
Outer Conductor Plating Specification	30 micro inches	
Body Material and Plating	Brass, Nickel	
Body Plating Specification	ASTM-B-733	

Environmental Specifications

Temperature

Operating Range -55 to +200 deg C

Compliance Certifications

(see [product page](#) for current document)

Plotted and Other Data

Notes:


Lead Free 1553 TRB 2-Slot Plug to Blunt Cut Genderless Cable Assembly using M17/176-00002 Coax, 5 FT with Bend Relief

LC3MSA00465-60



How to Order

Part Number Configuration:



Example: LC3MSA00465-12 = 12 inches long cable
LC3MSA00465-100cm = 100 cm long cable

Lead Free 1553 TRB 2-Slot Plug to Blunt Cut Genderless Cable Assembly using M17/176-00002 Coax, 5 FT with Bend Relief from L-com has same day shipment for domestic and International orders. L-com is a leading manufacturer of wired and wireless connectivity products and committed to in-stock availability and same day shipping. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

Lead Free 1553 TRB 2-Slot Plug to Blunt Cut Genderless Cable Assembly using M17/176-00002 Coax, 5 FT with Bend Relief

L-com CAD Drawing

LEAD FREE SOLDER

ZONE	REV
	A

-LABEL
SEE NOTE 1 & 2

LENGTH

BEND RELIEF

Technical drawing of a ribbon cable assembly. The assembly consists of a flat ribbon cable with a series of vertical vias and a metal ground plane. A rectangular connector is attached to one end. The drawing includes the following labels:

- LENGTH**: A dimension line indicating the total length of the cable.
- BEND RELIEF**: A label pointing to the area where the ribbon cable is bent to prevent damage.
- BLUNT CUT**: A label pointing to the end of the ribbon cable.
- LABEL SEE NOTE 1 & 2**: A label pointing to a small rectangular area on the ribbon cable, which contains the text `WWW.LCOM.COM` and `LCXXXXXX-XX`.

- M171176-00002, 78 OHM TWINAX CABLE
JACKET: PFA, BLUE
NOM. DIA: .129" [3.28]

—TRB 2-SI OT PI UG

WIRING MAP

NOTES

1. CABLE ASSY LENGTH LABEL PLACEMENT: 36 INCHES OR LESS, ONE LABEL APPROX CENTERED. LONGER THAN 36 INCHES, TWO LABELS APPROX 6 INCHES FROM EACH CONNECTOR.
CABLE ASSEMBLY LENGTH DETERMINED BY ILLUSTRATED:
LC3MSA00465-XX (XX = OAL IN INCHES)
CABLES ASSEMBLIES SHALL BE TESTED FOR CONTINUITY.
- 2.
- 3.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE, OR THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED.

			
<p>INTERPRET ALL DIMENSIONS TOLERANCES FOR ASME SCALE SHEET</p>			
<p>UNLESS OTHERWISE SPECIFIED, LEADING DIMENSIONS IN [] ARE MILLIMETERS TOLERANCES:</p>		<p>None 1 C</p>	
$X = \pm 0.2 [5]$ $XX = \pm 0.2 [5]$ $XXX = \pm 0.05 [0.13]$		FRACTIONS $\pm 1/32$ ANGLES: $\pm 1^\circ$	
CABLE LENGTH TOLERANCES: $\pm 12 [305] = \pm 12 [50]$ $\pm 12 [305] = \pm 60 [1524] = \pm 12 [51] - 0$ $> 12 [305] = \pm 12 [6124] = \pm 12 [1524] = \pm 12 [3048] = \pm 14 [3564] = \pm 16 [4512] - 0$ $> 60 [1524] = \pm 60 [4572] = \pm 12 [1524] = \pm 12 [3048] = \pm 14 [3564] = \pm 16 [4512] - 0$ $> 120 [3048] = \pm 120 [6124] = \pm 12 [1524] = \pm 12 [3048] = \pm 14 [3564] = \pm 16 [4512] - 0$		ANGLES: $\pm 1^\circ$ DESCRIPTION Lead Free Bend Relief 2-Slot TRB Plug with Blunt Cut 1553 C Using 78 Ohm M17176-00002 Twinax	
<p>an INFINITE[®] brand</p>		<p>Website: www.l-com.com Phone: 1.800.341.5266 1.978.682.6936</p>	
<p>ITEM NO.</p>		<p>LC3MSA00465</p>	
<p>DRAWN BY</p>		<p>KDANG</p>	
<p>SIZE</p>		<p>CAGE CODE</p>	
<p>A</p>		<p>43321</p>	

LC3MSA00465-60 REV 1.0 | © 2020 Infinite Electronics, Inc. L-com is a registered trademark of Infinite Electronics, Inc.