

LSZH 1553 TRB 3-Lug Jack to TRB 3-Lug Jack Cable
Assembly using TWCH-78-2 Coax, 3 FT with Bend Relief



LC3MSA00593-36

Configuration

- Connector 1: TRB 3-Lug Jack
- Connector 2: TRB 3-Lug Jack
- Cable Type: TWCH-78-2

Features

- MIL-STD-1553
- -30°C to +80°C
- 78 ohms
- ROHS Low Smoke Zero Halogen
- Non-Toxic

Applications

- Military Contractors
- MIL-STD-1553
- Data
- Safer Environments
- Ventilation critical areas
- Hospitals

Description

L-com's LC3MSA00593-36 is a LSZH 1553 TRB 3-Lug jack to TRB 3-Lug jack cable assembly using TWCH-78-2 coax, 3 FT with bend relief and ships same-day. These flexible RF cable assemblies are ideal for applications where flexure is required. Our L-com TRB 3-Lug to TRB 3-Lug cable assembly has a jack to jack gender configuration with 78 Ohm flexible TWCH-78-2 series coax and operates to 500 MHz.

Custom versions of this TRB 3-Lug jack to TRB 3-Lug jack cable, along with the rest of L-com's other RF assemblies, can also be built and shipped same day. Other available RF cable assembly value added services from L-com include connector orientation or clocking, heat shrink booting and custom labeling. RF testing can also be performed to document the electrical performance of your cable assembly. Contact a sales representative for testing or custom RF cable quotes. Part number LC3MSA00593-36 L-com LSZH 1553 TRB 3-Lug Jack to TRB 3-Lug Jack Cable Assembly using TWCH-78-2 Coax, 3 FT with Bend Relief data sheet PDF includes details of the RF product specifications, CAD drawing(s) and dimensions below.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		500	MHz
Capacitance		21.2 [69.55]		pF/ft [pF/m]
Operating Voltage (AC)			1,000	Vrms

Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency	10	50	100	200	500	MHz
Insertion Loss (Typ.)	0.266	0.353	0.425	0.515	0.68	dB

Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB per connector.

LSZH 1553 TRB 3-Lug Jack to TRB 3-Lug Jack Cable
Assembly using TWCH-78-2 Coax, 3 FT with Bend Relief



LC3MSA00593-36

Mechanical Specifications

Cable Assembly

Length*	36 in [914.4 mm]
Weight	0.24 lbs [108.86 g]

Cable

Cable Type	TWCH-78-2
Impedance	78 Ohms
Inner Conductor Type	Stranded
Inner Conductor Material and Plating	Copper, Silver
Dielectric Type	PE
Shield Layer 1	Silver Plated Copper
Jacket Material	HF POF, Blue

One Time Minimum Bend Radius	1.25 in [31.75 mm]
------------------------------	--------------------

Connectors

Description	Connector 1	Connector 2
Type	TRB 3-Lug Jack	TRB 3-Lug Jack
Impedance	78 Ohms	78 Ohms
Contact Material and Plating	Bronze, Gold 30 micro inches	Bronze, Gold 30 micro inches
Contact Plating Specification	ASTM-B-488	ASTM-B-488
Dielectric Type	Teflon	Teflon
Outer Conductor Material and Plating	Phosphor Bronze, Gold	Phosphor Bronze, Gold
Outer Conductor Plating Specification	30 micro inches	30 micro inches
Body Material and Plating	Brass, Nickel	Brass, Nickel
Body Plating Specification	ASTM-B-733	ASTM-B-733

Environmental Specifications

Temperature

Operating Range	-30 to +80 deg C
-----------------	------------------

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

LSZH 1553 TRB 3-Lug Jack to TRB 3-Lug Jack Cable
Assembly using TWCH-78-2 Coax, 3 FT with Bend Relief



LC3MSA00593-36

How to Order

Part Number Configuration: **LC3MSA00593** - **xx** **uu**

Unit of Measure:
cm = Centimeters
<blank> = Inches

Length

Base Number


Example: LC3MSA00593-12 = 12 inches long cable
LC3MSA00593-100cm = 100 cm long cable

LSZH 1553 TRB 3-Lug Jack to TRB 3-Lug Jack Cable Assembly using TWCH-78-2 Coax, 3 FT with Bend Relief from L-com has same day shipment for domestic and International orders. L-com is a leading manufacturer of wired and wireless connectivity products and committed to in-stock availability and same day shipping. Our portfolio includes coaxial cable assemblies, connectors, adapters and custom products as well as lightning and surge protectors, NEMA rated enclosures, and an RF product line which includes antennas, amplifiers, passive, and active components.

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. L-com reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. L-com does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and L-com does not assume liability arising out of the use of any part or document.

LSZH 1553 TRB 3-Lug Jack to TRB 3-Lug Jack Cable Assembly
using TWCH-78-2 Coax, 3 FT with Bend Relief

L-com CAD Drawing



UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE IN INCHES DIMENSIONS IN [] ARE MILLIMETERS		L-com® an INFINITE® brand Website: www.L-com.com Phone: 1.800.341.5266 1.978.682.6936		INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5	
TOLERANCES:		FRACTIONS		SCALE	
.X = ±.2 [5]		.XX = ±.02 [0.5]		NONE	
.XXX = ±.005 [0.13]		ANGLES ± 1°		SHEET	
CABLE LENGTH TOLERANCES:		FRACTIONS		1 OF 1	
≤12 [305] = +1 [25] / -0		.XX = ±.02 [0.5]			
>12 [305] ≤ 60 [1524] = +2 [51] / -0		.XXX = ±.005 [0.13]			
>60 [1524] ≤ 120 [3048] = +4 [102] / -0		CABLE LENGTH TOLERANCES:			
>120 [3048] ≤ 300 [7620] = +6 [152] / -0		≤12 [305] = +1 [25] / -0			
>300 [7620] = +5% / -0		>12 [305] ≤ 60 [1524] = +2 [51] / -0			
		>60 [1524] ≤ 120 [3048] = +4 [102] / -0			
		>120 [3048] ≤ 300 [7620] = +6 [152] / -0			
		>300 [7620] = +5% / -0			
ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE. UNDIMENSIONED NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION. COLORS MAY VARY.		DESCRIPTION		SIZE	
		LSZH Bend Relief 3-Lug TRB Jack to Jack 1553 Cable Using 78 Ohm TWCH-78-2 Twinax		A	
		CAGE CODE		ITEM NO.	
		43321		LC3MSA00593	
		DRAWN BY		REV	
		KDANG		A	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	
		5		6	
		1		2	
		3		4	