	ſ	8 7	6	5	+	4	3		2	1	
$ \begin{array}{c}   \\   \\   \\   \\   \\   \\   \\   \\   \\   $		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTIONS IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.									
	-	J									
C C C C C C C C C C C C C C	D										D
C C C C C C C C C C C C C C											
C C C C C C C C C C C C C C											
C C C C C C C C C C C C C C			-				-				
C C C PIN 5 PIN 4 PIN 5 PIN 5 P			.08	.45	[203.2]			.467			
C C PIN 5 PIN 4 PIN 4 PIN 4 PIN 4 PIN 4 PIN 4 PIN 5 PIN 4 PIN 5 PIN 4 PIN 5 PIN 4 PIN 5 PIN 4 PIN 5 PIN 4 PIN 5 PIN 5 PIN 4 PIN 5 PIN			[2.1]					[11.86] →			_
C C C D D D D D D D D D D D D D											
C PIN 6 PIN 6				/~\\\\			п	00			
B     Solve Average     Solve Average     NUT AND washer REMOVED FOR CLARITY       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average     Image: Solve Average     Image: Solve Average       B     Image: Solve Average	С							$\sim$ $\cdot$			С
B     SOLVE AND MALE CONCERNING     NUT AND WASHER     NUT AND WASHER       B     Image: Solve And And Solve And And Parts Nickel PlateD.     BODY     Image: Solve And And Solve And And Parts Nickel PlateD.       B     Image: Solve And And Solve And And Parts Nickel PlateD.     Image: Solve And And Solve And And Parts Nickel PlateD.     Image: Solve And And Solve And And Parts Nickel PlateD.       A     Solve And And Solve And And Parts Nickel PlateD.     Image: Solve And And Solve And And Parts Nickel PlateD.     Image: Solve And And Solve And And Parts Nickel PlateD.		PIN 6 MD66FSF PIN 4			//						
Image Note Cools and integration of the set of		6 POSITION		1/2-28	LINEE TINNE	D COPPER WIRE,	NUT	AND WASHER			
B B CLOCK WASHER LOCK WASHER LOCK WASHER B B DDY CLOCK WASHER B B CLOCK WASHER CLOCK WAS		A		1/2-28 H	0010	ei: pvC dr: see wire map	REMO		Y		
B PIN NUMBER WIRE COLOR PIN 1 BLACK PIN 2 WHITE PIN 2 WHITE PIN 4 GREEN PIN 4 GREEN PIN 6 BLUE NOTES: 1. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED. 2. REAR OF HOUSING IS PORTED. MATERIAL: SILCONE RESIN CONFORMAL MERSONERING SUPERVISED AND AND AND AND AND AND AND AND AND AN	->				ASHER			<u> </u>		-	€
B PIN NUMBER WIRE COLOR PIN 1 BLACK PIN 2 WHITE PIN 3 RED PIN 4 GREEN PIN 4 GREEN PIN 6 BLUE NOTES: 1. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED. 2. REAR OF HOUSING IS PORTED. MATERIAL: SILCONE RESIN CONFORMAL METAL OPENING											
B PIN 1 BLACK PIN 2 WHITE PIN 3 RED PIN 4 GREEN PIN 6 BLUE NOTES: 1. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED. 2. REAR OF HOUSING IS POTTED. MATERIAL: SILCONE RESIN CONFORMAL							ł	.475			
PIN 3       RED         PIN 4       GREEN         PIN 5       BROWN         PIN 6       BLUE         NOTES:       I. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED.         2. REAR OF HOUSING IS POTTED. MATERIAL: SILCONE RESIN CONFORMAL					$\left( \begin{array}{c}  abla .467 \\ \left( \left[ 11.86 \right] \right) \end{array} \right)$						
PIN 4       GREEN         PIN 5       BROWN         PIN 6       BLUE         NOTES:       I. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED.         2. REAR OF HOUSING IS POTTED. MATERIAL: SILCONE RESIN CONFORMAL	В				( [						В
PIN 6       BLUE       Image: State of the street in the street i		PIN 4 GREEN									
A PANEL OPENING PANEL OPENING A PANEL OPENING A PANEL OPENING A A A A A A A A A A A A A A A A A A A			<u> </u>								
NOTES:         1. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED.         2. REAR OF HOUSING IS POTTED. MATERIAL; SILCONE RESIN CONFORMAL							RI				
1. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED.         A         2. REAR OF HOUSING IS POTTED. MATERIAL: SILCONE RESIN CONFORMAL         DIMENSIONS ARE IN INCHES Immil DRAWNERY							17			-	_
1. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED.         A         2. REAR OF HOUSING IS POTTED. MATERIAL: SILCONE RESIN CONFORMAL         DIMENSIONS ARE IN INCHES Immil DELAWATERY											
1. FINISH OF EXTERNAL METAL PARTS NICKEL PLATED.         A         2. REAR OF HOUSING IS POTTED. MATERIAL: SILCONE RESIN CONFORMAL         DIMENSIONS ARE IN INCHES Imm											
A 2. REAR OF HOUSING IS POTTED. MATERIAL: SILCONE RESIN CONFORMAL											A
3. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY. A CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY. A CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKACED IN ACCORDANICE WITH >60(1524) 5103 10348 = +4 (102) /-0 >60(1524) 5103 10348 = +4 (102) /-0 DFRISELLO 06/25/2019	A		CONFORMAL				DIMENSIONS ARE IN			50 HIGH STREET	
							OVERALL CABLE LENGT ≤12 [305] = +1 [ >12 [305] ≤60 [1524] >60 [1524] ≤120 [3048] >120 [3048] <300 [7220]	H TOLERANCE: 25] / -0 = +2[51] / -0 = +4 [102] / -0 = +6 [152] / -0 APPROVED B'	06/25/2019 CATEGORY I/O PROD	DUCTS	

4. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

6

-5

4

B

8

|3048] <300 [7620] = +6 [15] >300 [7620] = +5% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08] .XX = ±.02 [.51] .XXX = ±.005 [.13] \_ 3

$\sim$		
• •		
_		







